

**COATED
BACK-LIT**

COMBanner

Features



B1 Fire Retardant Certified
REACH/ROHS Certified
Best Suited for LED Backlit Light Box
Matte & Glossy Surface Available
Vibrantly and Consistent Printing Quality

Technical Data Sheet

Item Code	FBCBFX5502828450	Test Method	
Base Fabric	500D*500D 28*28	DIN EN ISO2060	
Weight (GSM)	450	DIN EN ISO2286-2	
Tensile Strength	Warp (N/5cm)	1800	ISO527/3:1995
	Weft (N/5cm)	1700	ISO527/3:1995
Tear Strength	Warp (N/5cm)	180	ISO4674/1:2003
	Weft (N/5cm)	180	ISO4674/1:2003
Adhesion Strength	N/A	DIN53357:1982	
Temperature	-30°C/+70°C	ISO13934-1:1999	
RF Weldable (Heat Sealable)	YES	DIN53354	
Flame Retardant	B1/M1/M2/NFPA701		

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat: +86-15858322153
mailto:hncomax@163.com jeff@hncomax.com

